

Recommended Tools:

- Fine tooth saw or stanley knife
- Silicone Sealant
- Panel pins/Staples & Staple Gun/Adhesive
- Straight Edge
- Tape Measure
- Pencil

Panels & profiles MUST be checked for colour shading differences, flaws, defects or damage prior to installation.

1. Pre-installation

- a. Please check panels are from the same batch prior to installation. A batch number can be found on the back of each panel, as well as the outer packaging. Colour variation can occur between different batches, therefore all panels must be checked before fitting.
- b. ceilingPANEL is intended for use on the ceiling only. Using it on the wall will invalidate your warranty. Grant Westfield offer multiPANEL and tilePANEL for vertical application.
- c. To ensure your ceilingPANEL is properly bonded, ensure all surfaces to which adhesive will be applied are clean, dry and even.

2. Fitting panels and profiles

- a. ceilingPANEL may be pinned or stapled through the groove, or bonded direct to flat, smooth ceilings. If the ceiling surface is uneven, we recommend building a timber batten frame to apply the panels to.
- b. Start by attaching a Type M ceiling mould or Type L end cap as required to wall and ceiling joint.
- c. Apply a bead of silicone or sealant to the channel of the starting profile.
- d. If opting to glue panels to the ceiling or framework, apply adhesive to the back of the panel, and angle into the starting profile. Alternatively, locate the panel in position and staple or pin through the groove.
- e. Continue across the ceiling, using Type P clip-in trims or Type K mid-joints if required. In some cases it may be necessary to cut off the tongues or grooves before fitting.
- f. Finish by measuring and cutting the last panel, and applying a Type M ceiling mould or Type L end cap as required, prior to fixing to the ceiling.

3. Cutting panels

- a. ceilingPANEL should be cut using a fine-tooth blade hand-saw, decorative face up.

4. Down lighting

- a. PVC panels and profiles should not be subjected to temperatures in excess of 60°C. Doing so will invalidate your warranty.
- b. When fitting ceilingPANEL onto plasterboard, the aperture in the plasterboard should have a radius of approximately 60mm greater than the aperture in the ceilingPANEL.

5. Aftercare

- a. Once installed, your ceilingPANEL requires virtually no maintenance. Panels should be wiped clean with soft cloth or sponge, using a mild, non-abrasive detergent.